

Package ‘oddsratio’

June 13, 2019

Title Odds Ratio Calculation for GAM(M)s & GLM(M)s

Version 2.0.0

Date 2019-06-13

Description Simplified odds ratio calculation of GAM(M)s & GLM(M)s. Provides structured output (data frame) of all predictors and their corresponding odds ratios and confident intervals for further analyses. It helps to avoid false references of predictors and increments by specifying these parameters in a list instead of using 'exp(coef(model))' (standard approach of odds ratio calculation for GLMs) which just returns a plain numeric output. For GAM(M)s, odds ratio calculation is highly simplified with this package since it takes care of the multiple 'predict()' calls of the chosen predictor while holding other predictors constant. Also, this package allows odds ratio calculation of percentage steps across the whole predictor distribution range for GAM(M)s. In both cases, confident intervals are returned additionally. Calculated odds ratio of GAM(M)s can be inserted into the smooth function plot.

License MIT + file LICENSE

URL <https://github.com/pat-s/oddsratio>

BugReports <https://github.com/pat-s/oddsratio/issues>

Depends R (>= 3.0.0)

Imports ggplot2 (>= 3.0.0), mgcv, stats, stringr, tibble

Suggests cowplot, gam, grid, gtable, knitr, MASS, rmarkdown, scales, testthat

VignetteBuilder knitr

ByteCompile true

Encoding UTF-8

LazyData true

RoxygenNote 6.1.1

NeedsCompilation no

Author Patrick Schratz [aut, cre] (<<https://orcid.org/0000-0003-0748-6624>>)

Maintainer Patrick Schratz <patrick.schratz@gmail.com>

Repository CRAN

Date/Publication 2019-06-13 16:30:02 UTC

R topics documented:

insert_or	2
or_gam	4
or_glm	6
plot_gam	7

Index	10
--------------	-----------

insert_or	<i>Insert odds ratios of GAM(M)s into smoothing function</i>
-----------	--

Description

This function inserts calculated odds ratios of GAM(M)s into a plot of a GAM(M) smoothing function.

Usage

```
insert_or(plot_object = NULL, or_object = NULL, line_col = "red",
  line_size = 1.2, line_type = "solid", line_alpha = 1,
  text_alpha = 1, text_size = 4, text_col = "black",
  rect_alpha = 0.5, rect_col = NULL, rect = FALSE, arrow = TRUE,
  values = TRUE, values_yloc = 0, values_xloc = NULL, or_yloc = 0,
  arrow_length = NULL, arrow_yloc = NULL, arrow_col = NULL,
  arrow_xloc_r = NULL, arrow_xloc_l = NULL)
```

Arguments

plot_object	A ggplot object from plot_gam .
or_object	A tibble as returned from or_gam .
line_col, line_alpha, line_type, line_size	Aesthetics of vertical lines.
text_col, text_alpha, text_size	Aesthetics of inserted values.
rect_col, rect_alpha	Aesthetics of shaded rectangle.
rect	Logical. Whether to print a shaded rectangle between the vertical lines.
arrow	Logical. Whether to print arrows above the inserted values. Default to TRUE.

values	Logical. Whether to print predictor value information nearby the inserted vertical lines. Default to TRUE.
values_xloc	Numeric. X-axis location/shift of values relative to their vertical line. Default to 2% of x-axis range.
or_yloc, values_yloc	Numeric. Specifies y-location of inserted odds ratio / values. Relative to plotted y-axis range. A positive/negative value will place the the text higher/lower.
arrow_xloc_r, arrow_xloc_l, arrow_yloc, arrow_length, arrow_col	Numeric. Axis placement options of inserted arrows. Relative to respective axis ranges.

Details

The idea behind this function is to add calculated odds ratio of fitted GAM models ([or_gam](#)) into a plot showing the smooth function ([plot_gam](#)) of the chosen predictor for which the odds ratio was calculated for. Multiple insertions can be made by iteratively calling the function (see examples).

Right now the function does only accept results of [or_gam](#) with `slice = FALSE`. If you want to insert multiple odds ratio you have to do it iteratively.

Value

Returns a ggplot plotting object

Author(s)

Patrick Schratz patrick.schratz@gmail.com

See Also

[plot_gam](#)

[or_gam](#)

Examples

```
# load data (Source: ?mgcv::gam) and fit model
library(mgcv)
fit_gam <- gam(y ~ s(x0) + s(I(x1^2)) + s(x2) +
  offset(x3) + x4, data = data_gam) # fit model

# create input objects (plot + odds ratios)
library(oddsratio)
plot_object <- plot_gam(fit_gam, pred = "x2", title = "Predictor 'x2'")
or_object1 <- or_gam(
  data = data_gam, model = fit_gam,
  pred = "x2", values = c(0.099, 0.198)
)

# insert first odds ratios to plot
plot_object <- insert_or(plot_object, or_object1,
  or_yloc = 3,
```

```

    values_xloc = 0.04, line_size = 0.5,
    line_type = "dotdash", text_size = 6,
    values_yloc = 0.5, arrow_col = "red"
  )

  # calculate second odds ratio
  or_object2 <- or_gam(
    data = data_gam, model = fit_gam, pred = "x2",
    values = c(0.4, 0.6)
  )

  # add or_object2 into plot
  insert_or(plot_object, or_object2,
    or_yloc = 2.1, values_yloc = 2,
    line_col = "green4", text_col = "black",
    rect_col = "green4", rect_alpha = 0.2,
    line_alpha = 1, line_type = "dashed",
    arrow_xloc_r = 0.01, arrow_xloc_l = -0.01,
    arrow_length = 0.01, rect = TRUE
  )

```

or_gam

Calculate odds ratios of Generalized Additive (Mixed) Models

Description

This function calculates odds ratio(s) for specific increment steps of a GAM(M)s. Odds ratios can also be calculated for continuous percentage increment steps across the whole predictor distribution using `slice = TRUE`.

Usage

```

or_gam(data = NULL, model = NULL, pred = NULL, values = NULL,
        percentage = NULL, slice = FALSE, CI = NULL)

```

Arguments

<code>data</code>	The data used for model fitting.
<code>model</code>	A fitted GAM(M).
<code>pred</code>	Character. Predictor name for which to calculate the odds ratio.
<code>values</code>	Numeric vector of length two. Predictor values to estimate odds ratio from. Function is written to use the first provided value as the "lower" one, i.e. calculating the odds ratio 'from value1 to value2'. Only used if <code>slice = FALSE</code> .
<code>percentage</code>	Numeric. Percentage number to split the predictor distribution into. A value of 10 would split the predictor distribution by 10% intervals. Only needed if <code>slice = TRUE</code> .

slice	Logical. Default = FALSE. Whether to calculate odds ratios for fixed increment steps over the whole predictor distribution. See percentage for setting the increment values.
CI	Numeric. Currently fixed to 95% confidence interval level (2.5% - 97.5%). It should not be changed in a function call!

Details

Currently supported functions: [mgcv::gam](#), [mgcv::gamm](#), [gam::gam](#). For [mgcv::gamm](#), the model input of [or_gam](#) needs to be the gam output (e.g. `fit_gam$gam`).

Value

A data frame with (up to) eight columns. `perc1` and `perc2` are only returned if `slice = TRUE`:

predictor	Predictor name
value1	First value of odds ratio calculation
value2	Second value of odds ratio calculation
perc1	Percentage value of value1
perc2	Percentage value of value2
oddsratio	Calculated odds ratio(s)
CI_low	Lower (2.5%) confident interval of odds ratio
CI_high	Higher (97.5%) confident interval of odds ratio

Author(s)

Patrick Schratz patrick.schratz@gmail.com

See Also

[or_glm](#)
[plot_gam](#)
[insert_or](#)

Examples

```
# load data (Source: ?mgcv::gam) and fit model
library(mgcv)
fit_gam <- gam(y ~ s(x0) + s(I(x1^2)) + s(x2) +
  offset(x3) + x4, data = data_gam) # fit model

# Calculate OR for specific increment step of continuous variable
or_gam(
  data = data_gam, model = fit_gam, pred = "x2",
  values = c(0.099, 0.198)
)

## Calculate OR for change of indicator variable
```

```

or_glm(
  data = data_gam, model = fit_gam, pred = "x4",
  values = c("B", "D")
)

## Calculate ORs for percentage increments of predictor distribution
## (here: 20%)
or_glm(
  data = data_gam, model = fit_gam, pred = "x2",
  percentage = 20, slice = TRUE
)

```

or_glm

Calculate odds ratios of Generalized Linear (Mixed) Models

Description

This function calculates odds ratio(s) for specific increment steps of GLMs.

Usage

```
or_glm(data, model, incr, CI = 0.95)
```

Arguments

data	The data used for model fitting.
model	A fitted GLM(M).
incr	List. Increment values of each predictor.
CI	numeric. Which confident interval to calculate. Must be between 0 and 1. Default to 0.95

Details

CI_low and CI_high are only calculated for GLM models because [glmmPQL](#) does not return confident intervals due to its penalizing behavior.

Currently supported functions: [glm](#), [glmmPQL](#)

Value

A data frame with five columns:

predictor	Predictor name(s)
oddsratio	Calculated odds ratio(s)
CI_low	Lower confident interval of odds ratio
CI_high	Higher confident interval of odds ratio
increment	Increment of the predictor(s)

Author(s)

Patrick Schratz patrick.schratz@gmail.com

See Also

[or_gam](#)

Examples

```
## Example with glm()
# load data (source: http://www.ats.ucla.edu/stat/r/dae/logit.htm) and
# fit model
fit_glm <- glm(admit ~ gre + gpa + rank,
  data = data_glm,
  family = "binomial"
) # fit model

# Calculate OR for specific increment step of continuous variable
or_glm(data = data_glm, model = fit_glm, incr = list(gre = 380, gpa = 5))

# Calculate OR and change the confidence interval level
or_glm(
  data = data_glm, model = fit_glm,
  incr = list(gre = 380, gpa = 5), CI = .70
)

## Example with MASS:glmPQL()
# load data
library(MASS)
data(bacteria)
fit_glmPQL <- glmPQL(y ~ trt + week,
  random = ~ 1 | ID,
  family = binomial, data = bacteria,
  verbose = FALSE
)

# Apply function
or_glm(data = bacteria, model = fit_glmPQL, incr = list(week = 5))
```

Description

This function plots the smoothing function of selected GAM(M) models using the ggplot2 plotting system.


```
library(oddsratio)  
plot_gam(fit_gam, pred = "x2", title = "Predictor 'x2'")
```

Index

gam: :gam, 5
glm, 6
glmmPQL, 6

insert_or, 2, 5, 8

mgcv: :gam, 5
mgcv: :gamm, 5

or_gam, 2, 3, 4, 5, 7, 8
or_glm, 5, 6

plot_gam, 2, 3, 5, 7, 8

seq, 8

tibble, 2