

Package ‘switchr’

November 15, 2018

Type Package

Title Installing, Managing, and Switching Between Distinct Sets of Installed Packages

Version 0.13.5

Author Gabriel Becker[aut, cre]

Maintainer Gabriel Becker <gabembecker@gmail.com>

Copyright Genentech Inc

Description Provides an abstraction for managing, installing, and switching between sets of installed R packages. This allows users to maintain multiple package libraries simultaneously, e.g. to maintain strict, package-version-specific reproducibility of many analyses, or work within a development/production release paradigm. Introduces a generalized package installation process which supports multiple repository and non-repository sources and tracks package provenance.

Imports tools, RJSONIO, RCurl

Depends methods

SystemRequirements git, svn

License Artistic-2.0

URL <https://github.com/gmbecker/switchr>

BugReports <https://github.com/gmbecker/switchr/issues>

RoxygenNote 6.1.1

NeedsCompilation no

Repository CRAN

Date/Publication 2018-11-15 08:30:02 UTC

R topics documented:

.libPaths2	3
addPkg	4
archive_retries	5

archive_timing	5
BiocDevel	6
BiocRelease	7
biocReposForVers	7
BiocSVNManifest	8
BiocVers	9
branch	9
c.SessionManifest-method	10
checkIsPkgDir	10
cranPkgVersManifest	11
currentCompEnv	12
defaultRepos	12
dep_repos	13
dl_method	13
errorOrNonZero	14
fileFromFileURL	15
findNewestPkgInds	15
findPkgDir	16
findPkgVersionInRepo	16
flushSession	17
full_libpaths	18
getPkgDir	18
GithubManifest	19
gotoVersCommit	19
head	20
install_packages	21
lazyRepo	23
libManifest	25
LibraryProfile-class	26
library_paths	26
loadGRAN	27
loadManifest	27
locatePkgVersion	28
location	29
logfun	29
makeBiocSVNURL	30
makeFileURL	30
makeLibraryCtx	31
makeManifest	31
makePkgCheckout	32
makePkgDir	32
makeSeedMan	34
makeSource	35
manifest	35
ManifestRow	36
manifest_df	37
normalizePath2	37
notrack	38

nrow 39

packages 39

parsedSessionInfo-class 40

parseSessionInfoString 40

PkgManifest 40

pkgname 41

PkgSource-class 41

publishManifest 42

removeLib 43

RepoSubset 43

rVersionManifest 44

SessionManifest 45

shell_timing 45

sh_init_script 46

subdir 46

switchBack 47

switchDeps 47

switchrBaseDir 48

SwitchrCtx 48

switchrDontUnload 49

switchrManifest 49

switchrNoUnload 50

SwitchrParam-class 50

switchTo 51

system_w_init 53

updateManifest 54

update_PACKAGES 54

versions_df 56

Index **58**

<code>.libPaths2</code>	<i>.libpaths2</i>
-------------------------	-------------------

Description

A version of .libPaths which allows for excluding the site library

Usage

```
.libPaths2(fulllp, exclude.site = TRUE)
```

Arguments

- fulllp The libpath to use, as in .libPaths
- exclude.site logical. Should the site library be suppressed. Defaults to TRUE

Details

Behaves exactly as the `.libPaths` function does, with the exception of optionally excluding the site library

addPkg	<i>addPkg</i>
--------	---------------

Description

Add a package to an object associated with a manifest

Usage

```
addPkg(x, ..., rows = makeManifest(...), versions = data.frame(name =
  manifest_df(rows)$name, version = NA_character_, stringsAsFactors =
  FALSE), replace = FALSE)

## S4 method for signature 'PkgManifest'
addPkg(x, ..., rows = makeManifest(...),
  versions = data.frame(name = manifest_df(rows)$name, version =
  NA_character_, stringsAsFactors = FALSE), replace = FALSE)

## S4 method for signature 'SessionManifest'
addPkg(x, ..., rows = makeManifest(...),
  versions = data.frame(name = manifest_df(rows)$name, version =
  NA_character_, stringsAsFactors = FALSE), replace = FALSE)
```

Arguments

<code>x</code>	A manifest or manifest-associate object to add the package to
<code>...</code>	The information regarding the package to place in the manifest
<code>rows</code>	An already-created data.frame to add to the manifest
<code>versions</code>	A data.frame of package names and versions, if adding to a <code>SessionManifest</code> , ignored otherwise
<code>replace</code>	logical. If true, the specified package info will replace any already in the manifest in the case of duplicates. Otherwise, an error is thrown.

archive_retries	<i>archive_retries</i>
-----------------	------------------------

Description

Get or set the number of times to retry downloading a file from the CRAN archive

This is intended to stop intermittent install failures due to failing to retrieve files that **are** in the archive but are not downloading properly when a larger number of packages is being retrieved.

Usage

```
archive_retries(x)

## S4 method for signature 'SwitchrParam'
archive_retries(x)

archive_retries(x) <- value

## S4 replacement method for signature 'SwitchrParam'
archive_retries(x) <- value
```

Arguments

x	A SwitchrParam object
value	The new number of seconds to wait

Value

When getting, the number of seconds to wait, when setting, a new, updated SwitchrParam object.

archive_timing	<i>archive_timing</i>
----------------	-----------------------

Description

Get or set the number of seconds to wait after trying to retrieve a file from the CRAN Archive.

This is intended to stop intermittent install failures due to failing to retrieve files that **are** in the archive but are not downloading properly when a larger number of packages is being retrieved.

Usage

```
archive_timing(x)

## S4 method for signature 'SwitchrParam'
archive_timing(x)

archive_timing(x) <- value

## S4 replacement method for signature 'SwitchrParam'
archive_timing(x) <- value
```

Arguments

x	A SwitchrParam object
value	The new number of seconds to wait

Value

When getting, the number of seconds to wait, when setting, a new, updated SwitchrParam object.

BiocDevel

BiocDevel

Description

An object representing the current Bioc devel version. Can be passed to switchTo.

Usage

```
BiocDevel
```

Format

An object of class RepoSubset of length 1.

BiocRelease	<i>BiocRelease</i>
-------------	--------------------

Description

An object representing the current Bioc release. Can be passed to switchTo.

Usage

```
BiocRelease
```

Format

An object of class RepoSubset of length 1.

biocReposForVers	<i>biocReposForVers</i>
------------------	-------------------------

Description

Generate the URLs of the repositories associated with a specific Bioconductor release

Usage

```
biocReposForVers(version)
```

Arguments

version	The Bioconductor release to generate URLs for.
---------	--

Note

This function will only work if some version of Bioconductor (>2.9) was installed when switchr was installed. It will return NULL otherwise.

BiocSVNManifest *Create a manifest of Bioc SVN locations*

Description

Create a manifest of Bioc SVN locations

Usage

```
BiocSVNManifest(bioc_vers = "devel", software_only = TRUE)
```

Arguments

<code>bioc_vers</code>	A version number for a bioc release, or "devel" to for the current devel trunk
<code>software_only</code>	logical. Should only software packages be included in the manifest? Defaults to TRUE

Details

In combination with the `lazyRepo` function, this manifest can be used to work from a local, working checkout of a set of inter-dependent Bioconductor packages.

Value

A `PkgManifest` which contains SVN locations for all packages found in the specified bioc repositories, as well as those listed in `not_in_repo`

See Also

[lazyRepo](#)

Examples

```
## wrapped in try because it fails on some finnick build systems
bman = try(BiocSVNManifest())
bman
## Not run:
repo = lazyRepo("rtracklayer", bman)

## End(Not run)
```

BiocVers	<i>BiocVers</i>
----------	-----------------

Description

A constructor for creating a RepoSubset object for a specified release of Bioconductor, which includes only the BiocInstaller package.

Usage

```
BiocVers(version = getBiocReleaseVr(), name = paste("BioC", version,
  sep = "_"), repos = biocReposForVers(version))
```

Arguments

version	The version of Bioconductor
name	The default name for switchr libraries created with this object
repos	The urls of the Bioconductor repositories. these will be modified automatically to match the specified version

branch	<i>branch</i>
--------	---------------

Description

Get or set the branch associated with a Package Source

Usage

```
branch(x)

## S4 method for signature 'PkgSource'
branch(x)

branch(x) <- value

## S4 replacement method for signature 'PkgSource'
branch(x) <- value
```

Arguments

x	A source
value	The new branch

c,SessionManifest-method
cmethods

Description

Combine 2 or more manifests of the same type (PkgManifest or SessionManifest)

Usage

```
## S4 method for signature 'SessionManifest'
c(x, ..., recursive = FALSE)

## S4 method for signature 'PkgManifest'
c(x, ..., recursive = FALSE)
```

Arguments

x	An object (indicates the type of all objects to be combined)
...	more objects
recursive	Unused

checkIsPkgDir *Check if a directory contains package sources*

Description

Check if a directory contains package sources

Usage

```
checkIsPkgDir(dir)
```

Arguments

dir	The directory
-----	---------------

cranPkgVersManifest *cranPkgVersManifest*

Description

Create a Pkg manifest which points to tarballs representing a particular version of a CRAN package and versions of its (recursive) dependencies that were contemporary on the first or last day the specified package version resided on CRAN

Usage

```
cranPkgVersManifest(pkg, vers, earliest = TRUE,  
  cur_avail = available.packages(), verbose = FALSE,  
  suggests = c("direct", "none"), delay = 1)
```

Arguments

pkg	The package on which to base the generated manifest
vers	The version of pkg to construct the cohort around. Note this must match the the version string exactly, i.e. 1.3.1 and 1.3-1 are <i>*not*</i> equivalent.
earliest	Should the package dependencies be contemporary with the first (TRUE) or last (FALSE) day the specified package version was (the latest version) on CRAN?
cur_avail	The output from available.packages(). Used to identify whether the necessary version is in the CRAN archive or normal repository
verbose	Should debugging information about the recursive traversal of package dependencies be printed (defaults to FALSE).
suggests	Which Suggests'ed packages should be included. Currently supported possibilities are direct, indicating Suggestions of pkg should be included, and none, indicating that no Suggests'ed packages should be counted.
delay	Number of seconds to delay between successive REST calls to the cran database. Defaults to 1 second

Value

A SessionManifest object

Note

Some packages retain the same version on CRAN for long periods of time. The cohort in the manifest represents a gross proxy for the cohort used in conjunction within an analysis which used a the vers version of the specified package. In general it will **not** perfectly recreate the set of package versions originally used.

Author(s)

Gabriel Becker

References

"Gabor Csardi" (2014). `crandb`: Query the unofficial CRAN metadata database. R package version 1.0.0. <https://github.com/metacran/crandb>

Becker G, Barr C, Gentleman R, Lawrence M; Enhancing Reproducibility and Collaboration via Management of R Package Cohorts. *Journal of Statistical Software*, 81(1). 2017. doi: 10.18637/jss.v082.i01

Examples

```
## Not run:  
man = cranPkgVersManifest("devtools", "1.6")  
  
## End(Not run)
```

currentCompEnv	<i>currentCompEnv</i>
----------------	-----------------------

Description

Display the computing environment currently in use. If `switchTo` has not been called, a new `SwitchrCtx` object describing the current environment is created.

Usage

```
currentCompEnv()
```

defaultRepos	<i>defaultRepos</i>
--------------	---------------------

Description

Get default repositories for use as dependency repos and within `install_packages`

Usage

```
defaultRepos()
```

Value

A character vector of package repository urls

dep_repos	<i>dep_repos</i>
-----------	------------------

Description

Get or set repositories to be used to fulfill dependencies beyond packages within the manifest

Usage

```

dep_repos(x)

## S4 method for signature 'PkgManifest'
dep_repos(x)

## S4 method for signature 'SessionManifest'
dep_repos(x)

dep_repos(x) <- value

## S4 replacement method for signature 'PkgManifest'
dep_repos(x) <- value

## S4 replacement method for signature 'SessionManifest'
dep_repos(x) <- value

```

Arguments

x	A package or session manifest
value	A character vector with the new dependency repos

Value

Character vector with existing repository urls

d1_method	<i>d1_method</i>
-----------	------------------

Description

Get or set the download method for retrieving files.

Usage

```
dl_method(x)

## S4 method for signature 'SwitchrParam'
dl_method(x)

dl_method(x) <- value

## S4 replacement method for signature 'SwitchrParam'
dl_method(x) <- value
```

Arguments

x	A SwitchrParam object
value	The new number of seconds to wait

errorOrNonZero	<i>Identify error states from R or external programs</i>
----------------	--

Description

Identify error states from R or external programs

Usage

```
errorOrNonZero(out)
```

Arguments

out	An R object representing output
-----	---------------------------------

Value

TRUE if out is an error object, or has an attribute called "status" which is > 0

fileFromFileURL	<i>Get path from file URL</i>
-----------------	-------------------------------

Description

Get path from file URL

Usage

```
fileFromFileURL(fileurl)
```

Arguments

fileurl	A file url (beginning in file://)
---------	-----------------------------------

Value

The system directory path that fileurl points to

findNewestPkgInds	<i>Find newest packages in a package info data.frame</i>
-------------------	--

Description

Find newest packages in a package info data.frame

Usage

```
findNewestPkgInds(df, pkgcol = "package", verscol = "version")
```

```
findNewestPkgRows(df, pkgcol = "package", verscol = "version",
  newcol = "new", verbose = FALSE, logfun = message)
```

Arguments

df	data.frame. Table of package information
pkgcol	string. Name of column containing package name
verscol	string. Name of column containing package version in version-string form.
newcol	character. Experimental. column name for the column indicating that the version is new.
verbose	logical. Should debugging information be written using logfun during this process.
logfun	function. Logging function (closure) which should be called to write verbose logging messages during the process.

Value

a data.frame with the same columns as df which contains only the most recent row for each unique package name, as determined by the contents of df[[verscol]]

for findNewestPkgInds, the indices of the rows representing the newest version of each package within df. For findNewestPkgRows, the rows themselves from df representing the newest version of each package.

findPkgDir	<i>Find a package directory within an SCM checkout</i>
------------	--

Description

Find a package directory within an SCM checkout

Usage

```
findPkgDir(rootdir, branch, subdir, param)
```

Arguments

rootdir	The directory of the checkout
branch	The branch to navigate to
subdir	The subdirectory to navigate to
param	a SwitchrParam object

Value

A path to the Package sources

findPkgVersionInRepo	<i>findPkgVersionInRepo</i>
----------------------	-----------------------------

Description

findPkgVersionInRepo

Usage

```
findPkgVersionInRepo(repo, name, version, param, dir)
```

```
## S4 method for signature 'character'
findPkgVersionInRepo(repo, name, version, param, dir)
```

```
## S4 method for signature ``NULL``
findPkgVersionInRepo(repo, name, version, param, dir)
```


Arguments

repo	The repository
name	The name of the package
version	The version of the package to find
param	A SwitchrParam object
dir	The directory to download the located package tarball into

Value

A path to the downloaded tarball, or NULL

flushSession	<i>flushSession</i>
--------------	---------------------

Description

Unload currently loaded packages from the current R session

Usage

```
flushSession(dontunload = switchrDontUnload())
```

Arguments

dontunload	Non-base packages to ignore (not detach/unload)
------------	---

Details

Attached packages are detached (and unloaded) first. After this is done, loaded packages, such as those imported by (previously) attached packages, are unloaded.

Finally, after all packages have been unloaded, native libraries loaded by those packages are unloaded (on systems where this is supported).

Value

NULL, called for its side-effect of unloading packages

Note

Failing to include `switchr`, any of its dependencies, or any base packages (available as a vector in the `switchDeps` object) in `dontunload` will result in undefined, likely erroneous behavior.

full_libpaths	<i>full_libpaths</i>
---------------	----------------------

Description

Accessor for the full library path associate with a SwitchrCtx, including the R library and (if not excluded) the site library

Usage

```
full_libpaths(seed)
```

```
## S4 method for signature 'SwitchrCtx'
full_libpaths(seed)
```

Arguments

seed	a SwitchrCtx
------	--------------

getPkgDir	<i>Construct package directory path</i>
-----------	---

Description

Construct package directory path

Usage

```
getPkgDir(basepath, name, subdir, scm_type, branch)
```

Arguments

basepath	The parent directory for the package directory
name	The name of the package
subdir	The subdirectory within a package source that the actual package root directory will reside in.
scm_type	Type type of scm the package sources will be checked out from
branch	The branch from which the package will be retrieved.

Value

A path

Note

Unlike [findPkgDir](#) this does not look for existing package source directories. It only constructs the path.

GithubManifest	<i>GithubManifest</i>
----------------	-----------------------

Description

Create a package manifest containing only github packages

Usage

```
GithubManifest(..., pkgrepos)
```

Arguments

...	Combined to populate pkgrepos
pkgrepos	Github repositories in the form "<user>/<reponame>"

Details

Any names of the pkgrepos vector are assumed to be pkg names for the manifest. For unnamed elements, the pkg name is assumed to be the repository name.

Note

This is a convenience wrapper for [makeManifest](#). It uses the `username/repo[/subdir][@ref]` shorthand for specifying package locations in github repositories introduced by Wickham's devtools. Unlike devtools, username is not optional, and only branch names are currently supported in the `@ref`

Examples

```
ghman = GithubManifest("gmbecker/switchr", "hadley/devtools")
ghman
```

gotoVersCommit	<i>gotoVersCommit</i>
----------------	-----------------------

Description

This is a low-level function not intended for direct use by the end user.

Usage

```

gotoVersCommit(dir, src, version, param = SwitchrParam())

## S4 method for signature 'character,SVNSource'
gotoVersCommit(dir, src, version,
  param = SwitchrParam())

## S4 method for signature 'character,CRANSource'
gotoVersCommit(dir, src, version,
  param = SwitchrParam())

## S4 method for signature 'character,BiocSource'
gotoVersCommit(dir, src, version,
  param = SwitchrParam())

## S4 method for signature 'character,GitSource'
gotoVersCommit(dir, src, version,
  param = SwitchrParam())

```

Arguments

dir	Directory
src	A PkgSource (or subclass) object
version	The exact version to locate
param	A SwitchrParam

head	<i>Head and tail operations on manifests</i>
------	--

Description

Head and tail operations on manifests

Usage

```

head(x, ...)

## S4 method for signature 'SessionManifest'
head(x, n = 5, ...)

## S4 method for signature 'PkgManifest'
head(x, n = 5, ...)

tail(x, ...)

## S4 method for signature 'SessionManifest'

```

```
tail(x, n = 5, ...)

## S4 method for signature 'PkgManifest'
tail(x, n = 5, ...)
```

Arguments

x	A manifest object
...	unused
n	The number of packages to keep

Details

In the case of a `PkgManifest`, the first or last `n` packages are retained in the manifest, while all others are removed.

In the case of a `SessionManifest`, `n` specified versions are retained, while the underlying `PkgManifest` is unchanged.

Value

An object of the same type as `x` containing `n` packages

install_packages	<i>install_packages</i>
------------------	-------------------------

Description

Install packages from a set of traditional repositories, or a Just-in-time repository constructed using a `PkgManifest` or `SessionManifest`

Usage

```
install_packages(pkgs, repos, versions = NULL, verbose = FALSE, ...)

## S4 method for signature 'character,character'
install_packages(pkgs, repos,
  versions = NULL, verbose = FALSE, ...)

## S4 method for signature 'character,missing'
install_packages(pkgs, repos,
  versions = NULL, verbose = FALSE, ...)

## S4 method for signature 'SessionManifest,ANY'
install_packages(pkgs, repos,
  versions = NULL, verbose = FALSE, ...)

## S4 method for signature 'character,SessionManifest'
```

```
install_packages(pkgs, repos,
  versions = NULL, verbose = FALSE, ...)

## S4 method for signature 'character,PkgManifest'
install_packages(pkgs, repos,
  versions = NULL, verbose = FALSE, ...)
```

Arguments

pkgs	The names of the packages to install
repos	The (generalized) repositior(ies) to install the packages from. Can be a character vector of traditional package repositories (as with <code>install.packages</code>) or a <code>PkgManifest</code> or <code>SessionManifest</code> (or a url thereof)
versions	An optional named character vector or <code>data.frame</code> specifying exact versions of the packages to install
verbose	Should extra information be printed during the console during installation
...	extra parameters passed directly to <code>install.packages</code>

Details

In addition to installing the specified packages, this function annotates the installed DESCRIPTION files with provenance information about where the packages were installed from. This retains the information necessary to generate a manifest of installed packages for publication or reinstallation.

When `repos` is a vector of traditional repositories, this function - with the exception of the provenance mentioned above - behaves identically to `install.packages`. Otherwise, a Just-in-Time package repository is constructed using the information in the manifest(s) passed to `repos`, which is then used in conjunction with `link{install.packages}` to do the actual installation.

Author(s)

Gabriel Becker

References

Becker G, Barr C, Gentleman R, Lawrence M; Enhancing Reproducibility and Collaboration via Management of R Package Cohorts. *Journal of Statistical Software*, 81(1). 2017. doi: 10.18637/jss.v082.i01

Examples

```
## Not run:
## equivalent to install.packages, except it stores
## package provenance and knows about bioconductor repos
install_packages("nlme")

## install from a manifest
man = GithubManifest("gmbecker/fastdigest")
install_packages("fastdigest", man)

## install a full seeding manifest
```

```
man2 = makeSeedMan("myotherlib")
install_packages(man2)

## End(Not run)
```

lazyRepo

lazyRepo

Description

Create a lazy repository for installing directly from a package manifest. Most users will want to call `Install` directly, which will call this as needed behind the scenes.

Usage

```
lazyRepo(pkgs, pkg_manifest, versions = rep(NA, times = length(pkgs)),
  dir = tempdir(), rep_path = file.path(dir, "repo"),
  get_suggests = FALSE, verbose = FALSE,
  scm_auths = list(bioconductor = c("readonly", "readonly")),
  param = SwitchrParam(), force_refresh = FALSE)
```

```
## S4 method for signature 'SessionManifest,ANY'
lazyRepo(pkgs, pkg_manifest,
  versions = rep(NA, times = length(pkgs)), dir = tempdir(),
  rep_path = file.path(dir, "repo"), get_suggests = FALSE,
  verbose = FALSE, scm_auths = list(bioconductor = c("readonly",
  "readonly")), param = SwitchrParam(), force_refresh = FALSE)
```

```
## S4 method for signature 'PkgManifest,ANY'
lazyRepo(pkgs, pkg_manifest,
  versions = rep(NA, times = length(pkgs)), dir = tempdir(),
  rep_path = file.path(dir, "repo"), get_suggests = FALSE,
  verbose = FALSE, scm_auths = list(bioconductor = c("readonly",
  "readonly")), param = SwitchrParam(), force_refresh = FALSE)
```

```
## S4 method for signature 'character,SessionManifest'
lazyRepo(pkgs, pkg_manifest,
  versions = rep(NA, times = length(pkgs)), dir = tempdir(),
  rep_path = file.path(dir, "repo"), get_suggests = FALSE,
  verbose = FALSE, scm_auths = list(bioconductor = c("readonly",
  "readonly")), param = SwitchrParam(), force_refresh = FALSE)
```

```
## S4 method for signature 'character,PkgManifest'
lazyRepo(pkgs, pkg_manifest,
  versions = rep(NA, times = length(pkgs)), dir = tempdir(),
  rep_path = file.path(dir, "repo"), get_suggests = FALSE,
  verbose = FALSE, scm_auths = list(bioconductor = c("readonly",
  "readonly")), param = SwitchrParam(), force_refresh = FALSE)
```

Arguments

<code>pkgs</code>	The packages to install
<code>pkg_manifest</code>	The manifest to use
<code>versions</code>	Specific versions of the packages to install. Should be a vector of the same length as <code>pkgs</code> (and in the same order). Defaults to NA (any version) for all packages.
<code>dir</code>	The directory packages should be downloaded/checkedout/built into
<code>rep_path</code>	The path of the final repository
<code>get_suggests</code>	Whether suggested packages should be included in the lazy repository. Defaults to FALSE
<code>verbose</code>	Should extra information be printed to the user during the construction process
<code>scm_auths</code>	Named list of username/password credentials for checking out package sources from one or more sources listed in <code>manifest</code> . Defaults to readonly access to Bioconductor SVN
<code>param</code>	A <code>SwitchrParam</code> object
<code>force_refresh</code>	If a package already appears in the lazy repo area, it be updated (e.g. from SCM) and built again? Defaults to FALSE

Details

When checking building from SVN or git checkouts, this function will first look for existing checkouts for the relevant packages in `dir`. If found, these will be updated (in the case of conflicts, the behavior is undefined and will likely fail if they are not resolvable). This allows the user to have an existing, checkout directory where he or she works on development versions of multiple, inter-related packages, as local changes **WILL** be reflected in the packages built into the lazy repository.

Value

A path to the populated lazy repository, suitable for 'coercing' to a url and installing from.

Author(s)

Gabriel Becker

References

Becker G, Barr C, Gentleman R, Lawrence M; Enhancing Reproducibility and Collaboration via Management of R Package Cohorts. *Journal of Statistical Software*, 81(1). 2017. doi: 10.18637/jss.v082.i01

libManifest	<i>libManifest</i>
-------------	--------------------

Description

Create a Session- or PkgManifest for the contents of a switchr library.

Usage

```
libManifest(lib = currentCompEnv(), record_versions = TRUE,
  known_manifest = makeManifest(dep_repos = repos),
  repos = defaultRepos(), ...)
```

```
## S4 method for signature 'missing'
libManifest(lib = currentCompEnv(),
  record_versions = TRUE, known_manifest = makeManifest(dep_repos =
  repos), repos = defaultRepos(), ...)
```

```
## S4 method for signature 'character'
libManifest(lib = currentCompEnv(),
  record_versions = TRUE, known_manifest = makeManifest(dep_repos =
  repos), repos = defaultRepos(), ...)
```

```
## S4 method for signature 'SwitchrCtx'
libManifest(lib = currentCompEnv(),
  record_versions = TRUE, known_manifest = makeManifest(dep_repos =
  repos), repos = defaultRepos(), ...)
```

Arguments

lib	A SwitchrCtx object, or the name of a switchr library. Defaults to the currently active switchr library.
record_versions	Should the exact versions of installed packages be recorded in the manifest (TRUE)
known_manifest	An existing manifest, used when imputing location information for packages not installed via install_packages
repos	A vector of traditional package repositories. Used when imputing location information for packages not installed via install_packages
...	currently unused

Note

The manifest generated by this function will not include base packages, as they are part of R and not installable in the traditional sense.

Examples

```

man = libManifest()
man
## Not run:
man2 = libManifest("myotherlib")
man2

## End(Not run)

```

LibraryProfile-class *LibraryProfile (experimental)*

Description

Currently unused/under heavy development.

Details

An object

library_paths *library_paths*

Description

Accessor for which directories an SwitchrCtx is associated with.

Usage

```

library_paths(seed)

## S4 method for signature 'SwitchrCtx'
library_paths(seed)

```

Arguments

seed An SwitchrCtx

loadGRAN	<i>Load a GRAN repo package</i>
----------	---------------------------------

Description

Load a GRAN repo package

Usage

```
loadGRAN(nm = "current")
```

Arguments

nm The name of the repository for which to load the package. Defaults "current"

Details

This function is a convenience to load the package GRAN<nm>, which will provide the contained GRAN repository as default repository within the switchr framework.

Value

NULL. Called for the side-effect of loading the specified package

loadManifest	<i>loadManifest</i>
--------------	---------------------

Description

Load a package or session manifest from a file (local or URL)

Usage

```
loadManifest(fil)
```

Arguments

fil The path or URL to the file or a gist containing it

Value

A PkgManifest or SessionManifest object

locatePkgVersion	<i>locatePkgVersion</i>
------------------	-------------------------

Description

Locate and download/build the exact version of a single package.

Usage

```
locatePkgVersion(name, version, pkg_manifest, param = SwitchrParam(),  
  dir = notrack(repo), repo = NULL)
```

Arguments

name	package name
version	package version string
pkg_manifest	A manifest containing locations to search for the package
param	A SwitchrParam object
dir	directory to download package into
repo	(optional) GRANRepository object to search

Value

The full path to the downloaded file , or NULL if unable to locate the package

Note

Locating and attempting to install a non-current version of a single will not work in general, due to dependency issues. In most cases a Just-in-Time repository should be created and used instead, e.g. via [install_packages](#)

This function is called internally during the construction of Just-in-Time repositories and during the installation of specific package versions.

Author(s)

Gabriel Becker

location	<i>location</i>
----------	-----------------

Description

Retrieve the directory associated with an object

Usage

```
location(repo)
```

```
## S4 method for signature 'PkgSource'  
location(repo)
```

Arguments

repo An object associated with a path

Value

a character containing the associated path

Author(s)

Gabriel Becker

logfun	<i>logfun</i>
--------	---------------

Description

Get or set the logging function in an object associated with a SwitchrParam

Usage

```
logfun(x)
```

```
## S4 method for signature 'SwitchrParam'  
logfun(x)
```

```
logfun(x) <- value
```

```
## S4 replacement method for signature 'SwitchrParam'  
logfun(x) <- value
```

Arguments

x	An object with a SwitchrParam
value	The new logging function

makeBiocSVNURL	<i>Make a Bioconductor SVN url for a package</i>
----------------	--

Description

Make SVN url for a Bioconductor package given the name, bioc version, and type of package.

Usage

```
makeBiocSVNURL(name, biocVers = getBiocvrFromRvr(),
  pkgtype = "software")
```

Arguments

name	A vector of bioconductor package names The name of the package
biocVers	The version (release) of bioconductor, or 'trunk' (the default) for Bioc devel.
pkgtype	character. Which type of packages to retrieve the SVN root url for. Should be "software" or "data" for software and experimental data packages, respectively.

Value

A vector of urls for the specified packages within the Bioconductor SVN repository

makeFileURL	<i>make file url</i>
-------------	----------------------

Description

make file url

Usage

```
makeFileURL(path)
```

Arguments

path	The path to wrap in a file:// URL
------	-----------------------------------

Value

A valid file URL

makeLibraryCtx	<i>makeLibraryCtx</i>
----------------	-----------------------

Description

Locate or create a specified switchr library

Usage

```
makeLibraryCtx(name, seed = NULL, pkgs = NULL, exclude.site = TRUE,
               contains, rvers = NULL, verbose = FALSE)
```

Arguments

name	The name for the library
seed	The object to seed the library from
pkgs	Pkgs to install upon creation. Deprecated, use a seeding object instead.
exclude.site	Whether the site library should be excluded when switching to this library
contains	Currently unused.
rvers	Optional R version. If specified, existing libraries much be associated with the same R version to be considered a match.
verbose	Should informative messages be emitted to the console

Details

This function is not intended to be called directly in most cases; switchTo calls it automatically.

makeManifest	<i>Manifest constructor</i>
--------------	-----------------------------

Description

Create a package manifest

Usage

```
makeManifest(..., dep_repos = defaultRepos())
```

Arguments

...	Vectors containing package information. Passed to ManifestRow
dep_repos	The dependency repos for the package.

makePkgCheckout	<i>Create a checkout of a package and all it's dependencies from a manifest</i>
-----------------	---

Description

Create a checkout of a package and all it's dependencies from a manifest

Usage

```
makePkgCheckout(pkgs, pkg_manifest, dir, get_suggests = c("none",
  "first", "all"), param = SwitchrParam(),
  scm_auths = list(bioconductor = c("readonly", "readonly")),
  repos = defaultRepos())
```

Arguments

pkgs	character - The packages you will be working on
pkg_manifest	PkgmanifestlSessionManifest - The manifest containing the pkgs and dependencies to checkout
dir	character - The directory in which to place the checkouts of packages
get_suggests	character - Should 'Suggests' dependencies be retrieved? Options are "none" (never), "first" (for packages in pkgs but not for dependencies, or "all" (always).
param	SwitchrParam - The SwitchrParam to use during the checkout process,
scm_auths	list - A named list of user-password pairs to use during the checkout process
repos	character - The package repositories to retrieve dependency information from for pkgs/dependencies which do not appear in pkg_manifest

Value

a character vector of all packages (incl. recursive dependencies) checked out into dir

makePkgDir	<i>makePkgDir</i>
------------	-------------------

Description

This is an internal function not intended to be called directly by end users

Usage

```

makePkgDir(name, source, path, latest_only, param = SwitchrParam(),
  forceRefresh = FALSE)

## S4 method for signature 'ANY,SVNSource'
makePkgDir(name, source, path,
  latest_only = FALSE, param = SwitchrParam(), forceRefresh = FALSE)

## S4 method for signature 'ANY,GithubSource'
makePkgDir(name, source, path,
  latest_only = FALSE, param = SwitchrParam(), forceRefresh = FALSE)

## S4 method for signature 'ANY,GitSource'
makePkgDir(name, source, path,
  latest_only = FALSE, param = SwitchrParam(), forceRefresh = FALSE)

## S4 method for signature 'ANY,ANY'
makePkgDir(name, source, path, latest_only,
  param = SwitchrParam(), forceRefresh = FALSE)

## S4 method for signature 'ANY,CRANSource'
makePkgDir(name, source, path, latest_only,
  param = SwitchrParam(), forceRefresh = FALSE)

## S4 method for signature 'ANY,BiocSource'
makePkgDir(name, source, path, latest_only,
  param = SwitchrParam(), forceRefresh = FALSE)

## S4 method for signature 'ANY,TarballSource'
makePkgDir(name, source, path, latest_only,
  param = SwitchrParam(), forceRefresh = FALSE)

## S4 method for signature 'ANY,LocalSource'
makePkgDir(name, source, path, latest_only,
  param = SwitchrParam(), forceRefresh = FALSE)

```

Arguments

name	The package
source	A PkgSource
path	The path to place the directory
latest_only	Should a fastpath for downloading the latest commit in a SCM package without a formal checkout be used?
param	A SwitchrParam
forceRefresh	Should an existing instance of the package source be deleted/refreshed

Details

Create a directory and populate it with package source code from the specified source

makeSeedMan	<i>makeSeedMan</i>
-------------	--------------------

Description

makeSeedMan

Usage

```
makeSeedMan(x, known_manifest = PkgManifest(), ...)

## S4 method for signature 'missing'
makeSeedMan(x, known_manifest = PkgManifest(), ...)

## S4 method for signature 'sessionInfo'
makeSeedMan(x, known_manifest = PkgManifest(),
  ...)

## S4 method for signature 'parsedSessionInfo'
makeSeedMan(x,
  known_manifest = PkgManifest(), ...)

## S4 method for signature 'data.frame'
makeSeedMan(x, known_manifest = PkgManifest(),
  ...)
```

Arguments

x	The object to generate a seeding manifest from, if missing, the output from sessionInfo() is used.
known_manifest	A manifest containing known locations of package sources. makeSeedMan will attempt to determine locations of packages listed in x using both known_manifest and official repositories.
...	Currently unused.

Examples

```
man = makeSeedMan()
```

makeSource	<i>Create a PkgSource object for a package</i>
------------	--

Description

Create a PkgSource object for a package

Usage

```
makeSource(url, type, user, password, scm_auth = list(),
           prefer_svn = FALSE, ...)
```

Arguments

url	The url of the package sources
type	The source type.
user	A function which, when called, returns the username to use when checking the sources out
password	A function which returns the password to use when checking out the sources
scm_auth	A list of username-password pairs, named with regular expressions to match against url when constructing the defaults for user and password
prefer_svn	Currently unused.
...	Passed directly to constructors for PkgSource superclasses

manifest	<i>Get or set the manifest associated with an object</i>
----------	--

Description

Get or set manifest associated with an object

Usage

```
manifest(x)

manifest(x) <- value

## S4 method for signature 'SessionManifest'
manifest(x)

## S4 replacement method for signature 'SessionManifest'
manifest(x) <- value
```

Arguments

x	An object which contains a manifest
value	A PkgManifest

Value

A PkgManifest or SessionManifest object

ManifestRow

ManifestRow

Description

Create one or more rows of a manifest data.frame

Usage

```
ManifestRow(name, url = NA_character_, type = NA_character_,
            branch = NA_character_, subdir = ".", extra = NA_character_)
```

Arguments

name	name of the package.
url	location of the package sources
type	type of location (svn, git, local, etc)
branch	name of the branch to use to build the package
subdir	subdirectory to use to build the package
extra	currently ignored. extra commands for building or installing the package

Details

If name is missing, an empty (0 row) manifest data.frame is returned. All other fields default to values indicating no information- NA_character in most cases, and "." for subdir

Value

A valid Package manifest data.frame

manifest_df	<i>manifest_df</i>
-------------	--------------------

Description

Get or set the package location manifest (data.frame) associated with an object

Usage

```
manifest_df(x, ...)

## S4 method for signature 'SessionManifest'
manifest_df(x, session_only = TRUE, ...)

## S4 method for signature 'PkgManifest'
manifest_df(x)

manifest_df(x) <- value

## S4 replacement method for signature 'SessionManifest'
manifest_df(x) <- value

## S4 replacement method for signature 'PkgManifest'
manifest_df(x) <- value
```

Arguments

x	The object
...	unused.
session_only	Only return manifest rows associated with
value	A data.frame of package manifest information. See ManifestRow

normalizePath2	<i>normalizePath2</i>
----------------	-----------------------

Description

Attempt to normalize a relative path to an absolute one. Optionally without resolving symlinks on non-Windows systems

Usage

```
normalizePath2(path, follow.symlinks = FALSE, winslash = "\\",
  mustWork = NA)
```

Arguments

path	The path to normalize
follow.symlinks	Should symlinks (other than . and ..) be resolved to their physical locations? (FALSE)
winslash	The value of winslash to be passed down to normalizePath on windows systems
mustWork	logical. Passed to normalizePath on windows. Ignored otherwise.

Value

The normalized path.

notrack	<i>Notrack directory</i>
---------	--------------------------

Description

This function is not intended to be called directly by the user.

Usage

```
notrack(repo)

## S4 method for signature '`NULL`'
notrack(repo)
```

Arguments

repo	The object.
------	-------------

Value

the path where retrieved package versions should be. If repo is NULL, a notrack directory is constructed within a temp directory.

nrow	<i>Number of rows</i>
------	-----------------------

Description

Number of rows

Usage

```
nrow(x)

## S4 method for signature 'PkgManifest'
nrow(x)

## S4 method for signature 'SessionManifest'
nrow(x)
```

Arguments

x A tabular data structure.

Value

The number of rows in the structure

packages	<i>packages</i>
----------	-----------------

Description

List the packages installed in a switchr context (library)

Usage

```
packages(seed)

## S4 method for signature 'SwitchrCtx'
packages(seed)
```

Arguments

seed A switchr context

parsedSessionInfo-class

Parsed sessionInfo output

Description

An object representing the information in printed sessionInfo() output

parseSessionInfoString

Parse text output from printing SessionInfo objects

Description

Parse text output from printing SessionInfo objects

Usage

```
parseSessionInfoString(string)
```

Arguments

string The text output from sessionInfo()

PkgManifest

PkgManifest

Description

Construct a PkgManifest, which can be installed from using [install_packages](#)

Usage

```
PkgManifest(manifest = ManifestRow(...), dep_repos = defaultRepos(),
            ..., dl_method)
```

Arguments

manifest	The manifest (data.frame) of packages and their locations
dep_repos	A list of traditional pkg repositories which can contain dependencies for the packages listed in manifest.
...	Arguments passed to ManifestRow if manifest is not specified
dl_method	Download method. Ignored unless manifest is a character scalar containing a URL to a serialized manifest

Details

If a package is found in both the manifest data.frame and the dependency repositories, the version in the manifest will always take precedence within the switchr framework.

pkgname	<i>pkgname</i>
---------	----------------

Description

Get or set the package name associated with a Package Source

Usage

```
pkgname(x)

## S4 method for signature 'PkgSource'
pkgname(x)

pkgname(x) <- value

## S4 replacement method for signature 'PkgSource'
pkgname(x) <- value
```

Arguments

x	A source
value	The new pkgname

PkgSource-class	<i>PkgSource</i>
-----------------	------------------

Description

An object representing the source location of a package. This is a virtual used exclusively through its subclasses, which are used to differentiate the different types of package source locations.

publishManifest *publishManifest*

Description

Publish a package or session manifest to file.

Usage

```
publishManifest(manifest, dest = "./pkg_manifest.rman", ...)
```

```
## S4 method for signature 'PkgManifest,character'
```

```
publishManifest(manifest,
  dest = "./pkg_manifest.rman", ...)
```

```
## S4 method for signature 'SessionManifest,character'
```

```
publishManifest(manifest,
  dest = "./pkg_manifest.rman", ...)
```

```
## S4 method for signature 'missing,ANY'
```

```
publishManifest(manifest,
  dest = "./pkg_manifest.rman", ...)
```

```
## S4 method for signature 'SwitchrCtx,ANY'
```

```
publishManifest(manifest,
  dest = "./pkg_manifest.rman", ...)
```

Arguments

manifest	The object to save as a serialized package or session manifest. Default to the currently in use switchr library. A session manifest will be generated by libManifest as necessary.
dest	The destination manifest will be published to. Typically a character value indicating a file name (including path) to write to.
...	Unused

Value

The name of the file written

removeLib	<i>removeLib</i>
-----------	------------------

Description

Remove a switchr library and update the manifest of existing libraries

Usage

```
removeLib(name = NULL, repos = NULL, compEnv = NULL,
          fromStack = FALSE)
```

Arguments

name	The name of the switchr library to remove
repos	the url used to seed the library
compEnv	a SwitchrCtx representing the library to remove
fromStack	Whether the library should be removed if it currently appears in the Context stack Defaults to false.

Value

NULL, called for its side-effect of removing/destroying a switchr library

Note

Only one of name, repos and compEnv should be specified. An error will be thrown otherwise.

Examples

```
## Not run:
removeLib("mylibrary")

## End(Not run)
```

RepoSubset	<i>RepoSubset</i>
------------	-------------------

Description

An object that represents a subset of packages available in a repo. When switched to, switchr will default to only installing the specified packages, rather than all packages in the repository.

Usage

```
RepoSubset(repos, pkgs, default_name)
```

Arguments

<code>repos</code>	The traditional repositories to select the packages from
<code>pkgs</code>	The packages included in the subset
<code>default_name</code>	The default name to use when the RepoSubset is used to seed a switchr context

<code>rVersionManifest</code>	<i>rVersionManifest</i>
-------------------------------	-------------------------

Description

Create a Pkg manifest which points to tarballs representing the cohort of packages associated with a particular release of R

Usage

```
rVersionManifest(vers, curr_avail = available.packages())
```

Arguments

<code>vers</code>	The version of R to create a manifest for
<code>curr_avail</code>	The output from <code>available.packages()</code> . Used to identify whether the necessary version is in the CRAN archive or normal repository

Value

A SessionManifest object

Author(s)

Gabriel Becker

References

"Gabor Csardi" (2014). `crandb`: Query the unofficial CRAN metadata database. R package version 1.0.0. <https://github.com/metacran/crandb>

Becker G, Barr C, Gentleman R, Lawrence M; Enhancing Reproducibility and Collaboration via Management of R Package Cohorts. *Journal of Statistical Software*, 81(1). 2017. doi: 10.18637/jss.v082.i01

Examples

```
## Not run:
man = rVersionManifest("3.1.1")
man

## End(Not run)
```

SessionManifest	<i>SessionManifest</i>
-----------------	------------------------

Description

A manifest which includes both a PkgManifest containing package source information, and a data.frame defining a filter with exact versions of some or all packages

Usage

```
SessionManifest(manifest, versions = character())
```

Arguments

manifest	A PkgManifest
versions	A data.frame with 2 columns: name and version, or a named character vector. In the case of a character vector, the names are taken to be package names

Value

A SessionManifest object

shell_timing	<i>Get or set the number of seconds to wait between successive shell commands</i>
--------------	---

Description

This is intended to stop intermittent install failures due to network drive latency interacting with git commands

Usage

```
shell_timing(x)

## S4 method for signature 'SwitchrParam'
shell_timing(x)

shell_timing(x) <- value

## S4 replacement method for signature 'SwitchrParam'
shell_timing(x) <- value
```

Arguments

x	A SwitchrParam object
value	The new number of seconds to wait

Value

When getting, the number of seconds to wait, when setting, a new, updated SwitchrParam object.

sh_init_script	<i>shell init</i>
----------------	-------------------

Description

Set or Retrieve the shell initialization script for an object

Usage

```
sh_init_script(x)

## S4 method for signature 'SwitchrParam'
sh_init_script(x)

sh_init_script(x) <- value

## S4 replacement method for signature 'SwitchrParam'
sh_init_script(x) <- value
```

Arguments

x	An object associated with a SwitchrParam object
value	The new value.

subdir	<i>subdir</i>
--------	---------------

Description

accessor for subdirectory.

Usage

```

subdir(x)

## S4 method for signature 'PkgSource'
subdir(x)

subdir(x) <- value

## S4 replacement method for signature 'PkgSource'
subdir(x) <- value

```

Arguments

x	An object associated with a subdirectory, typically a PkgSource
value	The new subdirectory to associate with the object

switchBack	<i>switchBack</i>
------------	-------------------

Description

A convenience function to switch back to the previously used computing environment.

Usage

```
switchBack()
```

switchDeps	<i>switchrDeps</i>
------------	--------------------

Description

The base packages, as well as switchr and its dependencies.

Usage

```
switchDeps
```

Format

An object of class character of length 20.

switchrBaseDir	<i>Get or set the base directory for switchr libraries</i>
----------------	--

Description

Get or set the base directory for switchr libraries

Usage

```
switchrBaseDir(value)
```

Arguments

value	A new value for the base directory
-------	------------------------------------

Details

If value is missing, the current base directory is returned. Otherwise the value is set as the default directory and returned.

SwitchrCtx	<i>SwitchrCtx</i>
------------	-------------------

Description

A constructor for class SwitchrCtx, representing a switchr installed-package library.

Usage

```
SwitchrCtx(name, libpaths, exclude.site = TRUE, seed = NULL)
```

Arguments

name	The name to associate with the context
libpaths	The directories where the installed packages are located
exclude.site	Should the current site library be included in the context when it is switched to (TRUE) ’
seed	An object representing the list of packages the switchr context was seeded with.

References

Becker G, Barr C, Gentleman R, Lawrence M; Enhancing Reproducibility and Collaboration via Management of R Package Cohorts. *Journal of Statistical Software*, 81(1). 2017. doi: 10.18637/jss.v082.i01

switchrDontUnload	<i>Get or set packages to not unload when flushing the system</i>
-------------------	---

Description

Get or set packages which should NOT be unloaded when flushing the system, e.g., when switching between libraries.

Usage

```
switchrDontUnload(value, add = TRUE)
```

Arguments

value	The packages to not unload when switching libraries.
add	Should value be added to the existing list?

Note

By default switchr will not attempt to unload any base packages, itself, or any of its dependencies. Attempting to unload any of these packages (e.g. add=FALSE) will result in undefined behavior and is not recommended.

switchrManifest	<i>switchrManifest</i>
-----------------	------------------------

Description

Generate a manifest of all currently available (existing) switchr libraries.

Usage

```
switchrManifest()
```

Value

A data.frame with information about the located switchr libraries

Note

This function reads cached metadata from the current switchr base directory (~/.switchr by default). This cache is updated whenever the switchr framework is used to create or destroy a switchr library, but will not be updated if one is added or removed manually. In such cases [updateManifest](#) must be called first

switchrNoUnload	<i>Skip unloading of packages in session</i>
-----------------	--

Description

Set whether or not ANY packages are unloaded when switching libraries.

Usage

```
switchrNoUnload(value)
```

Arguments

value	A logical value, or missing to return the current option
-------	--

Details

This should be set to TRUE when using switchr in the context of dynamic documents such as .Rnw and .Rmd files.

Value

A logical indicating whether or not calling flushSession will be skipped during the library switching process.

SwitchrParam-class	<i>SwitchrParam</i>
--------------------	---------------------

Description

A constructor for a SwitchrParam object representing a number of common parameters understood by the switchr framework

Usage

```
SwitchrParam(logfun = function(...) NULL, shell_init = character(),
  archive_timing = 2, archive_retries = 2, dl_method,
  shell_timing = 1)
```

Arguments

logfun	The function to be called to write to logs
shell_init	A character containing the location of a shell script to be sourced before any system commands.
archive_timing	The timeout after downloading a package from the CRAN Archive.
archive_retries	Number of times to retry retrieving a package from the CRAN Archive.
dl_method	The download method to use when retrieve package source files. See download.file . If none is specified, the method defaults to "curl" if the RCurl package is installed and "auto" otherwise.
shell_timing	numeric. The numer of seconds to wait between certain shell commands. Defaults to 1, this should only need to be changed in the case of, e.g., networked drive latency issues.

Value

A SwitchrParam object.

Author(s)

Gabriel Becker

switchTo	<i>switchTo</i>
----------	-----------------

Description

Switch to a different computing environment (set of installed R packages and library location paths for new pkg installs)

Usage

```
switchTo(name, seed = NULL, reverting = FALSE,
         ignoreRVersion = FALSE, exclude.site = TRUE, ...)

## S4 method for signature 'character,character'
switchTo(name, seed = NULL,
         reverting = FALSE, ignoreRVersion = FALSE, exclude.site = TRUE,
         ...)

## S4 method for signature 'character,SwitchrCtx'
switchTo(name, seed = NULL,
         reverting = FALSE, ignoreRVersion = FALSE, exclude.site = TRUE,
         ...)
```

```
## S4 method for signature 'character,missing'
switchTo(name, seed = NULL,
  reverting = FALSE, ignoreRVersion = FALSE, exclude.site = TRUE,
  ...)

## S4 method for signature 'SwitchrCtx,ANY'
switchTo(name, seed = NULL,
  reverting = FALSE, ignoreRVersion = FALSE, exclude.site = TRUE,
  ...)

## S4 method for signature 'character,RepoSubset'
switchTo(name, seed = NULL,
  reverting = FALSE, ignoreRVersion = FALSE, exclude.site = TRUE,
  ...)

## S4 method for signature 'character,PkgManifest'
switchTo(name, seed = NULL,
  reverting = FALSE, ignoreRVersion = FALSE, exclude.site = TRUE,
  ...)

## S4 method for signature 'character,SessionManifest'
switchTo(name, seed = NULL,
  reverting = FALSE, ignoreRVersion = FALSE, exclude.site = TRUE,
  ...)
```

Arguments

name	The name associated (or to associate) with the computing environment.
seed	The seed, indicating packages to install into a newly created package library. No effect if the library already exists.
reverting	Indicates whether we are reverting to the environment in use before the current one. Typically not set directly by the user.
ignoreRVersion	Should the R version in use be ignored when checking for existing computing environments. This is experimental.
exclude.site	Should the Site library be excluded when creating and switching to the specified library. Defaults to TRUE.
...	Passed directly to <code>makeLibraryCtx</code> if an existing computing environment is not found.

Details

If `switchr` does not know about the specified computing environment, a new one will be created via `installCompEnv`. This includes creating a directory under the `switchr` base directory and installing packages into it. See `installCompEnv` for more details.

This function has the side effect of unloading all loaded packages (other than base packages, `GRAN` or `GRANBase`, `switchr` itself, and `switchr`'s dependencies) and the associated DLLs. It also changes the library location R will use to search for packages, e.g. when you call `library`.

This means you will have to reinstall packages after switching, which is important and intended (e.g. when switching to using Bioc devel from Bioc release).

Value

Invisibly returns the SwitchrCtx object representing the new computing environment

Note

By default, this process involves a call to `flushSession` which will attempt to unload all loaded packages. While some support of configuring what is unloaded is provided via `switchrDontUnload`, it is recommended that you turn this feature entirely off via `switchrNoUnload(TRUE)` when using `switchr` within dynamic documents (.Rnw/.Rmd files, etc), particularly when using the `knitr` package.

References

Becker G, Barr C, Gentleman R, Lawrence M; Enhancing Reproducibility and Collaboration via Management of R Package Cohorts. *Journal of Statistical Software*, 81(1). 2017. doi: 10.18637/jss.v082.i01

See Also

[makeLibraryCtx](#)

Examples

```
## Not run:
switchTo("mynewlibrary")
switchBack()

fdman = GithubManifest("gmbecker/fastdigest")
switchTo("fastdigestlib", seed = fdman)

## End(Not run)
```

system_w_init

system_w_init

Description

Run a system command with an optional initialization script (e.g. a `.bashrc` sourced first).

Usage

```
system_w_init(cmd, dir, init = character(), args = NULL, env = NULL,
  ..., param = SwitchrParam())
```

Arguments

cmd	The text of the command. Must be length 1.
dir	The directory that the command should be executed in. The working directory will be temporarily changed to this dir, but will be changed back upon exit of system_w_init.
init	(optional) a character value indicating the location of an initialization shell script.
args	character. Arguments to be passed to the command
env	character. Environmental variables to be set when running the command
...	additional parameters passed directly to system .
param	A SwitchrParam object. The shell initialization script associated with this object is used when init is not specified (length 0).

Value

Depends, see [system](#) for details.

updateManifest	<i>updateManifest</i>
----------------	-----------------------

Description

Update the cached information regarding available switchr libraries.

Usage

updateManifest()

Value

NULL, used for it's side-effect of updating the switchr library metadata cache.

update_PACKAGES	<i>update existing package repository</i>
-----------------	---

Description

Update an existing repository by reading the PACKAGES file and only processing built package tarballs which do not match existing entries.

update_PACKAGES can be much faster than write_PACKAGES for small-moderate changes to large repository indexes.

Usage

```
update_PACKAGES(dir = ".", fields = NULL, type = c("source",
  "mac.binary", "win.binary"), verbose = dryrun, unpacked = FALSE,
  subdirs = FALSE, latestOnly = TRUE, addFiles = FALSE,
  strict = TRUE, dryrun = FALSE, logfun = message, ...)
```

Arguments

dir	See write_PACKAGES
fields	See write_PACKAGES
type	See write_PACKAGES
verbose	Should informative messages be displayed throughout the process. Defaults to the value of dryrun (whose own default is FALSE) NOT passed to write_PACKAGES
unpacked	See write_PACKAGES
subdirs	See write_PACKAGES
latestOnly	See write_PACKAGES
addFiles	See write_PACKAGES
strict	logical. Should 'strict mode' be used when checking existing PACKAGES entries. See details. Defaults to TRUE.
dryrun	logical. Should should the necessary updates be calculated but NOT applied. (default FALSE)
logfun	function. If verbose is TRUE, the function to be used to emit the informative messages. Defaults to message
...	Additional arguments to write_PACKAGES - e.g., the relatively new rds_compress argument.

Details

Throughout this section, *package tarball* is taken to mean a tarball file in *dir* whose name can be interpreted as `<package>_<version>.<ext>` (or that is pointed to by the `File` field of an existing PACKAGES entry). *Novel package tarballs* are those which do not match an existing PACKAGES file entry.

update_PACKAGES avoids (re)processing package tarballs in cases where a PACKAGES file entry already exists and appears to remain valid. The logic for detecting still-valid entries is as follows:

Currently update_PACKAGES calls directly down to write_PACKAGES (and thus no speedup should be expected) if any of the following conditions hold:

- No PACKAGES file exists under *dir*
- `unpacked` is TRUE
- `subdirs` is anything other than FALSE
- `fields` is not NULL and one or more specified fields are not present in the existing PACKAGES file

All package tarballs whose last modify times are later than that of the existing PACKAGES file are considered novel and no attempt is made to identify or retain any corresponding PACKAGES entries. Similarly, all PACKAGES entries which have no corresponding package tarball are definitionally invalid.

When `strict = TRUE`, PACKAGES entries which appear to match a package tarball are confirmed via MD5 checksum; those that pass are retained as valid. All novel package tarballs are fully processed by the standard `write_PACKAGES` machinery, and the resulting entries are added. Finally, if `latestOnly = TRUE`, package-version pruning is performed across the entries.

When `strict = FALSE`, package tarballs are assumed to encode correct metadata in their filenames. PACKAGES entries which appear to match a package tarball are retained as valid (No MD5sum checking occurs). If `latestOnly = TRUE`, package-version pruning across the full set of retained entries and novel package tarballs *before* the processing of the novel tarballs, at significant computational and time savings in some situations. After the optional pruning, any relevant novel package tarballs are processed via `write_PACKAGES` and added to the set of retained entries.

After the above process concludes, the final database of PACKAGES entries is written to all three PACKAGES files, overwriting the existing files.

Note

While both strict and nonstrict modes offer speedups when updating small percentages of large repositories, non-strict mode is *much* faster and is recommended in situations where the assumptions it makes are safe.

Author(s)

Gabriel Becker

See Also

[write_PACKAGES](#)

versions_df

versions_df

Description

Get or set the the versions information in a SessionManifest

Usage

```
versions_df(x)

## S4 method for signature 'SessionManifest'
versions_df(x)

versions_df(x) <- value
```



```
## S4 replacement method for signature 'SessionManifest'  
versions_df(x) <- value
```

Arguments

x	An object containing package version information
value	A data.frame of package version information.

Index

*Topic **datasets**

- BiocDevel, [6](#)
- BiocRelease, [7](#)
- switchDeps, [47](#)
- .libPaths2, [3](#)

- addPkg, [4](#)
- addPkg,PkgManifest (addPkg), [4](#)
- addPkg,PkgManifest-method (addPkg), [4](#)
- addPkg,SessionManifest (addPkg), [4](#)
- addPkg,SessionManifest-method (addPkg), [4](#)
- archive_retries, [5](#)
- archive_retries,SwitchrParam (archive_retries), [5](#)
- archive_retries,SwitchrParam-method (archive_retries), [5](#)
- archive_retries<- (archive_retries), [5](#)
- archive_retries<-,SwitchrParam (archive_retries), [5](#)
- archive_retries<-,SwitchrParam-method (archive_retries), [5](#)
- archive_timing, [5](#)
- archive_timing,SwitchrParam (archive_timing), [5](#)
- archive_timing,SwitchrParam-method (archive_timing), [5](#)
- archive_timing<- (archive_timing), [5](#)
- archive_timing<-,SwitchrParam (archive_timing), [5](#)
- archive_timing<-,SwitchrParam-method (archive_timing), [5](#)

- BiocDevel, [6](#)
- BiocRelease, [7](#)
- biocReposForVers, [7](#)
- BiocSource-class (PkgSource-class), [41](#)
- BiocSVNManifest, [8](#)
- BiocVers, [9](#)
- branch, [9](#)
- branch,PkgSource (branch), [9](#)
- branch,PkgSource-method (branch), [9](#)
- branch<- (branch), [9](#)
- branch<-,PkgSource (branch), [9](#)
- branch<-,PkgSource-method (branch), [9](#)

- c,PkgManifest-method (c,SessionManifest-method), [10](#)
- c,SessionManifest-method, [10](#)
- checkIsPkgDir, [10](#)
- cranPkgVersManifest, [11](#)
- CRANSource-class (PkgSource-class), [41](#)
- currentCompEnv, [12](#)
- CVSSource-class (PkgSource-class), [41](#)

- defaultRepos, [12](#)
- dep_repos, [13](#)
- dep_repos,PkgManifest (dep_repos), [13](#)
- dep_repos,PkgManifest-method (dep_repos), [13](#)
- dep_repos,SessionManifest (dep_repos), [13](#)
- dep_repos,SessionManifest-method (dep_repos), [13](#)
- dep_repos<- (dep_repos), [13](#)
- dep_repos<-,PkgManifest (dep_repos), [13](#)
- dep_repos<-,PkgManifest-method (dep_repos), [13](#)
- dep_repos<-,SessionManifest (dep_repos), [13](#)
- dep_repos<-,SessionManifest-method (dep_repos), [13](#)
- dl_method, [13](#)
- dl_method,SwitchrParam (dl_method), [13](#)
- dl_method,SwitchrParam-method (dl_method), [13](#)
- dl_method<- (dl_method), [13](#)
- dl_method<-,SwitchrParam (dl_method), [13](#)
- dl_method<-,SwitchrParam-method (dl_method), [13](#)

- download.file, [51](#)
- errorOrNonZero, [14](#)
- fileFromFileURL, [15](#)
- findNewestPkgInds, [15](#)
- findNewestPkgRows (findNewestPkgInds), [15](#)
- findPkgDir, [16, 18](#)
- findPkgVersionInRepo, [16](#)
- findPkgVersionInRepo, character (findPkgVersionInRepo), [16](#)
- findPkgVersionInRepo, character-method (findPkgVersionInRepo), [16](#)
- findPkgVersionInRepo, NULL (findPkgVersionInRepo), [16](#)
- findPkgVersionInRepo, NULL-method (findPkgVersionInRepo), [16](#)
- flushSession, [17](#)
- full_libpaths, [18](#)
- full_libpaths, SwitchrCtx (full_libpaths), [18](#)
- full_libpaths, SwitchrCtx-method (full_libpaths), [18](#)
- getPkgDir, [18](#)
- GithubManifest, [19](#)
- GithubSource-class (PkgSource-class), [41](#)
- GitSource-class (PkgSource-class), [41](#)
- gotoVersCommit, [19](#)
- gotoVersCommit, character, BiocSource (gotoVersCommit), [19](#)
- gotoVersCommit, character, BiocSource-method (gotoVersCommit), [19](#)
- gotoVersCommit, character, CRANSource (gotoVersCommit), [19](#)
- gotoVersCommit, character, CRANSource-method (gotoVersCommit), [19](#)
- gotoVersCommit, character, GitSource (gotoVersCommit), [19](#)
- gotoVersCommit, character, GitSource-method (gotoVersCommit), [19](#)
- gotoVersCommit, character, SVNSource (gotoVersCommit), [19](#)
- gotoVersCommit, character, SVNSource-method (gotoVersCommit), [19](#)
- head, [20](#)
- head, PkgManifest (head), [20](#)
- head, SessionManifest (head), [20](#)
- head, SessionManifest-method (head), [20](#)
- install.packages, [22](#)
- install_packages, [21, 25, 28, 40](#)
- install_packages, character, character (install_packages), [21](#)
- install_packages, character, character-method (install_packages), [21](#)
- install_packages, character, missing (install_packages), [21](#)
- install_packages, character, missing-method (install_packages), [21](#)
- install_packages, character, PkgManifest (install_packages), [21](#)
- install_packages, character, PkgManifest-method (install_packages), [21](#)
- install_packages, character, SessionManifest (install_packages), [21](#)
- install_packages, character, SessionManifest-method (install_packages), [21](#)
- install_packages, SessionManifest, ANY (install_packages), [21](#)
- install_packages, SessionManifest, ANY-method (install_packages), [21](#)
- lazyRepo, [8, 23](#)
- lazyRepo, character, PkgManifest (lazyRepo), [23](#)
- lazyRepo, character, PkgManifest-method (lazyRepo), [23](#)
- lazyRepo, character, SessionManifest (lazyRepo), [23](#)
- lazyRepo, character, SessionManifest-method (lazyRepo), [23](#)
- lazyRepo, PkgManifest, ANY (lazyRepo), [23](#)
- lazyRepo, PkgManifest, ANY-method (lazyRepo), [23](#)
- lazyRepo, SessionManifest, ANY (lazyRepo), [23](#)
- lazyRepo, SessionManifest, ANY-method (lazyRepo), [23](#)
- libManifest, [25](#)
- libManifest, character (libManifest), [25](#)
- libManifest, character-method (libManifest), [25](#)
- libManifest, missing (libManifest), [25](#)

- libManifest,missing-method
(libManifest), 25
- libManifest,SwitchrCtx (libManifest), 25
- libManifest,SwitchrCtx-method
(libManifest), 25
- library_paths, 26
- library_paths,SwitchrCtx
(library_paths), 26
- library_paths,SwitchrCtx-method
(library_paths), 26
- LibraryProfile-class, 26
- loadGRAN, 27
- loadManifest, 27
- LocalSource-class (PkgSource-class), 41
- locatePkgVersion, 28
- location, 29
- location,PkgSource-method (location), 29
- logfun, 29
- logfun,SwitchrParam (logfun), 29
- logfun,SwitchrParam-method (logfun), 29
- logfun<- (logfun), 29
- logfun<-, SwitchrParam (logfun), 29
- logfun<- , SwitchrParam-method (logfun),
29

- makeBiocSVNURL, 30
- makeFileURL, 30
- makeLibraryCtx, 31, 53
- makeManifest, 19, 31
- makePkgCheckout, 32
- makePkgDir, 32
- makePkgDir, ANY, ANY (makePkgDir), 32
- makePkgDir, ANY, ANY-method (makePkgDir),
32
- makePkgDir, ANY, BiocSource (makePkgDir),
32
- makePkgDir, ANY, BiocSource-method
(makePkgDir), 32
- makePkgDir, ANY, CRANSource (makePkgDir),
32
- makePkgDir, ANY, CRANSource-method
(makePkgDir), 32
- makePkgDir, ANY, GithubSource
(makePkgDir), 32
- makePkgDir, ANY, GithubSource-method
(makePkgDir), 32
- makePkgDir, ANY, GitSource (makePkgDir),
32
- makePkgDir, ANY, GitSource-method
(makePkgDir), 32
- makePkgDir, ANY, LocalSource
(makePkgDir), 32
- makePkgDir, ANY, LocalSource-method
(makePkgDir), 32
- makePkgDir, ANY, SVNSource (makePkgDir),
32
- makePkgDir, ANY, SVNSource-method
(makePkgDir), 32
- makePkgDir, ANY, TarballSource
(makePkgDir), 32
- makePkgDir, ANY, TarballSource-method
(makePkgDir), 32
- makeSeedMan, 34
- makeSeedMan, data.frame (makeSeedMan), 34
- makeSeedMan, data.frame-method
(makeSeedMan), 34
- makeSeedMan, missing (makeSeedMan), 34
- makeSeedMan, missing-method
(makeSeedMan), 34
- makeSeedMan, parsedSessionInfo
(makeSeedMan), 34
- makeSeedMan, parsedSessionInfo-method
(makeSeedMan), 34
- makeSeedMan, sessionInfo (makeSeedMan),
34
- makeSeedMan, sessionInfo-method
(makeSeedMan), 34
- makeSource, 35
- manifest, 35
- manifest, SessionManifest (manifest), 35
- manifest, SessionManifest-method
(manifest), 35
- manifest<- (manifest), 35
- manifest<- , SessionManifest (manifest),
35
- manifest<- , SessionManifest-method
(manifest), 35
- manifest_df, 37
- manifest_df, PkgManifest (manifest_df),
37
- manifest_df, PkgManifest-method
(manifest_df), 37
- manifest_df, SessionManifest
(manifest_df), 37
- manifest_df, SessionManifest-method
(manifest_df), 37

- manifest_df<- (manifest_df), 37
- manifest_df<- ,PkgManifest (manifest_df), 37
- manifest_df<- ,PkgManifest-method (manifest_df), 37
- manifest_df<- ,SessionManifest (manifest_df), 37
- manifest_df<- ,SessionManifest-method (manifest_df), 37
- ManifestRow, 31, 36, 37, 40
- normalizePath2, 37
- notrack, 38
- notrack,NULL (notrack), 38
- notrack,NULL-method (notrack), 38
- nrow, 39
- nrow,PkgManifest (nrow), 39
- nrow,PkgManifest-method (nrow), 39
- nrow,SessionManifest (nrow), 39
- nrow,SessionManifest-method (nrow), 39
- packages, 39
- packages,SwitchrCtx (packages), 39
- packages,SwitchrCtx-method (packages), 39
- parsedSessionInfo-class, 40
- parseSessionInfoString, 40
- PkgManifest, 40
- PkgManifest-class (PkgManifest), 40
- pkgname, 41
- pkgname,PkgSource (pkgname), 41
- pkgname,PkgSource-method (pkgname), 41
- pkgname<- (pkgname), 41
- pkgname<- ,PkgSource (pkgname), 41
- pkgname<- ,PkgSource-method (pkgname), 41
- PkgSource-class, 41
- publishManifest, 42
- publishManifest,missing,ANY (publishManifest), 42
- publishManifest,missing,ANY-method (publishManifest), 42
- publishManifest,PkgManifest,character (publishManifest), 42
- publishManifest,PkgManifest,character-method (publishManifest), 42
- publishManifest,SessionManifest,character (publishManifest), 42
- publishManifest,SessionManifest,character-method (publishManifest), 42
- publishManifest,SwitchrCtx,ANY (publishManifest), 42
- publishManifest,SwitchrCtx,ANY-method (publishManifest), 42
- removeLib, 43
- RepoSubset, 43
- RepoSubset-class (RepoSubset), 43
- rVersionManifest, 44
- SessionManifest, 45
- SessionManifest-class (SessionManifest), 45
- sh_init_script, 46
- sh_init_script,SwitchrParam (sh_init_script), 46
- sh_init_script,SwitchrParam-method (sh_init_script), 46
- sh_init_script<- (sh_init_script), 46
- sh_init_script<- ,SwitchrParam,ANY (sh_init_script), 46
- sh_init_script<- ,SwitchrParam-method (sh_init_script), 46
- shell_timing, 45
- shell_timing,SwitchrParam (shell_timing), 45
- shell_timing,SwitchrParam-method (shell_timing), 45
- shell_timing<- (shell_timing), 45
- shell_timing<- ,SwitchrParam (shell_timing), 45
- shell_timing<- ,SwitchrParam-method (shell_timing), 45
- subdir, 46
- subdir,PkgSource (subdir), 46
- subdir,PkgSource-method (subdir), 46
- subdir<- (subdir), 46
- subdir<- ,PkgSource (subdir), 46
- subdir<- ,PkgSource-method (subdir), 46
- SVNSource-class (PkgSource-class), 41
- switchBack, 47
- switchDeps, 17, 47
- switchrBaseDir, 48
- SwitchrCtx, 48
- SwitchrCtx-class (SwitchrCtx), 48
- switchrDontUnload, 49
- switchrManifest, 49
- switchrNoUnload, 50
- SwitchrParam (SwitchrParam-class), 50

SwitchrParam-class, [50](#)
 switchTo, [51](#)
 switchTo, character, character
 (switchTo), [51](#)
 switchTo, character, character-method
 (switchTo), [51](#)
 switchTo, character, missing (switchTo),
 [51](#)
 switchTo, character, missing-method
 (switchTo), [51](#)
 switchTo, character, PkgManifest
 (switchTo), [51](#)
 switchTo, character, PkgManifest-method
 (switchTo), [51](#)
 switchTo, character, RepoSubset
 (switchTo), [51](#)
 switchTo, character, RepoSubset-method
 (switchTo), [51](#)
 switchTo, character, SessionManifest
 (switchTo), [51](#)
 switchTo, character, SessionManifest-method
 (switchTo), [51](#)
 switchTo, character, SwitchrCtx
 (switchTo), [51](#)
 switchTo, character, SwitchrCtx-method
 (switchTo), [51](#)
 switchTo, SwitchrCtx, ANY (switchTo), [51](#)
 switchTo, SwitchrCtx, ANY-method
 (switchTo), [51](#)
 system, [54](#)
 system_w_init, [53](#)

 tail (head), [20](#)
 tail, PkgManifest (head), [20](#)
 tail, PkgManifest-method (head), [20](#)
 tail, SessionManifest (head), [20](#)
 tail, SessionManifest-method (head), [20](#)
 TarballSource-class (PkgSource-class),
 [41](#)

 update_PACKAGES, [54](#)
 updateManifest, [49](#), [54](#)

 versions_df, [56](#)
 versions_df, SessionManifest
 (versions_df), [56](#)
 versions_df, SessionManifest-method
 (versions_df), [56](#)
 versions_df<- (versions_df), [56](#)

 versions_df<- , SessionManifest
 (versions_df), [56](#)
 versions_df<- , SessionManifest-method
 (versions_df), [56](#)

 write_PACKAGES, [56](#)